

GardenjoyTM

effortless gardening

AUTO REWIND HOSE REEL NW-10S / NW-15S / NW-20S / NW-30S

LOCATION

- Find a suitable position to install your Retractable Hose Reel
- Please take the following into account;
 - The structure you mount the unit on must be of solid and sound construction, which will not be upended when extending the unit.
 - The unit must be able to rotate 180 degrees.
 - Ensure that there are no obstacles in the immediate surroundings that will prevent the hose to be extended.
 - Mount the unit at a convenient height.
 - Mount the unit no further from the water source as what the connecting hose will allow.
 - Should your garden exceed double the maximum length of the extended hose try to place the unit in the center.
 - Mount the unit in such a position that it is not subjected to extreme conditions such as direct sun light, extreme heat or cold.
- The unit is supplied with two mounting brackets, consider the following;
 - Use one in the front and the other at the back of the dwelling to ensure optimum use.
 - Install multiple fixed source points if your furthest point exceeds more than double the maximum extended length – or install a second unit.

INSTALLATION

- Tools required;
 - Power Drill with suitable 8mm Drill Bit
 - Hammer.
 - No 10 Spanner or Adjustable Wrench.
 - Pencil.
 - Spirit Level.
 - Safety equipment during installation – Eye and ear protection and suitable gloves.
- Installation.
 - Place the mounting bracket against the wall, ensure that it is level and mark the holes.
NOTE: The unit will always swivel to its lowest point if the bracket is not mounted level.
 - Drill all holes with an 8mm masonry drill bit, at least 70mm deep.
 - Remove all the dust from the hole and insert the provided plugs.
 - Mount the bracket with the provided M6 x 60 Coach Screws and washers. Take

- care not to overtighten the screws as it could crack the mounting bracket.
- Connect the unit to the water source with the provided connection.

OPERATION

- Extending
 - Connect the unit to the water source.
 - Open the valve.
 - Extend the hose to the point required and allow the hose to return back slightly, the mechanism will click as the hose is locked into position.
 - Open the nozzle and water.
- Further extending,
 - Gently extend the hose until the next point is reached and allow the hose to return back slightly, the mechanism will click as the hose is locked into position.
- Retraction.
 - It is recommended that the unit is retracted after use – it will prolong the life of your hose as it not exposed to extreme weather conditions (UV rays / freezing)
 - Close the valve at the source, disconnect the unit and open the nozzle - this will allow all the water to run out as the hose is retracted.
 - Pull the hose slightly further out until the lock is released.
 - Slowly and in a controlled manner allow the unit to retract until fully retracted.
 - It is recommended to wipe the hose clean during retraction as to prevent grime and dirt entering the unit – it will prolong the life span.

WARNINGS

- Wear recommended protection during installation.
- **Do not** allow uninstructed / untrained persons to operate the unit.
- **Do not** allow children to play with the unit it is not a toy. Always supervise when used by children.
- **Do not** wear loose clothing or untied hair as this could become entangled and be pulled into the unit resulting in bodily injury.
- **Do not** allow the hose to retract uncontrolled as this could;
 - Result in bodily injury to man or animal.
 - Will damage the unit and render the warranty null and void.
- **Do not** over extend the unit past its maximum length.
- **Do Not** open the unit. This will result in bodily injury and will render the warranty null and void.
- The unit is for domestic use only and not suitable for communal / commercial or industrial use.
- Water pressure may not exceed 7 Bar.

WARRANTY

Please refer to the Product Warranty Policy on the Website at www.star-line.co.za

Copy right rest in NA Manufacturing (Pty) Ltd